


- 1. WHEN SPECIFIED ON THE APPROVED PLANS, THE SOLID METAL COVER FOR CATCH BASIN SHALL BE FURNISHED IN PLACE OF THE GRATE PROVIDED FOR ON STANDARD PLAN 5-5.
- 2. RAISED DESIGNS OTHER THAN THE DIAMOND DESIGN SHOWN HEREON MAY BE USED IF APPROVED BY THE ENGINEER.
- 3. CAST IN THE LETTERS "DRAIN" IN 2" RAISED LETTERS, 1/8" HIGH.
- 4. TO BE USED WITH FRAME SHOWN IN STANDARD PLAN 5-4.
- 5. PROVIDE 2-5/8" DIAMETER STAINLESS STEEL ALLEN TYPE BOLTS COUNTER SUNK FLUSH WITH COVER. (SEE STANDARD PLAN 5-4 FOR BOLT-DOWN CATCH BASIN FRAME).
- FRAME, CAST IRON ASTM A48 CL30, COVER, DUCTILE IRON ASTM A 536 GR 8055-06 H-20 RATED.



NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION IS KEPT ON FILE AT THE CITY OF KENT. A COPY MAY BE OBTAINED UPON REQUEST.

	CITY OF KENT ENGINEERING DEPARTMENT	
KENT		TCH BASIN VER
DESIGNEDDWH	SCALE NONE	STANDARD PLAN
DRAWNBB	-	
CHECKED	DATE	5_9
APPROVED	ENGINEER	J-3