



PUBLIC CATCH BASIN MARKER




PRIVATE CATCH BASIN MARKER

NOTE:

1. CATCH BASIN MARKER SHALL BE AFFIXED WITH MANUFACTURER'S EPOXY IN DRY WEATHER, 40 DEGREES AND WARMER. IF CURB EXISTS, MARKER IS PLACED ON TOP OF CURB. IF RAISED EDGE PAVEMENT, MARKER PLACEMENT IS ON THE WEDGE. IF NEITHER EXIST, MARKER WILL BE PLACED ON SIDE LEAST EXPOSED TO TRAFFIC.

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION IS KEPT ON FILE AT THE CITY OF KENT. A COPY MAY BE OBTAINED UPON REQUEST.



| | | |
|--|---|---------------|
|  | CITY OF KENT ENGINEERING DEPARTMENT | |
| | STORM DRAIN MARKERS | |
| DESIGNED <u>COK</u> | SCALE <u>NONE</u> | STANDARD PLAN |
| DRAWN <u>COK</u> | DATE <u>12/2019</u> | 5-37 |
| CHECKED <u>COK</u> | ENGINEER | |
| APPROVED _____ | | |