


**SPECIFICATIONS:**

- SIZE: 48 INCHES BY 24 INCHES
- MATERIAL: 0.125-GAUGE ALUMINUM
- FACE: REFLECTIVE WHITE 3M ENGINEERING GRADE WITH 3M ANTI-GRAFFITI SHEETING OVER SIGN
- COLORS: MULTI ON WHITE
- POST: 14 GAGE METAL SQUARE, 2"x2" MOUNTED WITH CORNER BOLTS AND GALVANIZED 3/8" WASHERS WITH A NEOPRENE WASHER TO THE FACE OF THE SIGN
- INSTALLATION: SECURE TO CHAIN LINK FENCE IF AVAILABLE. OTHERWISE INSTALL ON TWO METAL POSTS, PER KENT STANDARD PLAN 6-82a WITH THE TOP OF SIGN HIGHER THAN 42 INCHES FROM GROUND SURFACE.
- PLACEMENT: FACE SIGN IN DIRECTION OF PRIMARY VISUAL OR PHYSICAL ACCESS. DO NOT BLOCK ANY ACCESS ROAD. DO NOT PLACE WITHIN 6 FEET OF STRUCTURAL FACILITIES (E.G. MANHOLES, SPILLWAYS, PIPE INLETS).

*NOTE: IF THE FACILITY HAS A LINER TO RESTRICT INFILTRATION OF STORMWATER, THE FOLLOWING NOTE MUST BE ADDED TO THE FACE OF THE SIGN: "THIS FACILITY IS LINED TO PROTECT GROUNDWATER QUALITY." IN ADDITION, SPECIFIC INFORMATION ABOUT THE LINER MUST BE ADDED TO THE BACK OF THE SIGN AS SPECIFIED IN THE CURRENT SURFACE WATER DESIGN MANUAL SECTION 6.2.4.*

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION IS KEPT ON FILE AT THE CITY OF KENT. A COPY MAY BE OBTAINED UPON REQUEST.



	<b>CITY OF KENT</b> ENGINEERING DEPARTMENT	
	<b>STORMWATER POND SIGN</b>	
DESIGNED: COK	SCALE: NONE	STANDARD PLAN
DRAWN: COK	DATE: 12/2019	<b>5-40</b>
CHECKED: COK	ENGINEER	
APPROVED:		