



NOTES:

1. ISLAND REQUIRED ON EYEBROWS WITH AN OUTER RADIUS GREATER THAN 40'.
2. MINIMUM ISLAND DIAMETER SHALL BE 10'.
3. ISLAND SHALL HAVE VERTICAL CURB.
4. CEMENT CONCRETE ROLLED CURB MAY BE USED ON THE EYEBROW WITH TRANSITION PER STD. PLAN 6-33. WHEN ROLLED CURB IS USED THE SIDEWALK DEPTH SHALL INCREASE FROM 4" TO 6".
5. NO PARKING WITHIN 20' OF THE URBAN EYEBROW.
6. NO DRIVEWAYS ALLOWED WITHIN 5' OF CURB TRANSITION.

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION IS KEPT ON FILE AT THE CITY OF KENT. A COPY MAY BE OBTAINED UPON REQUEST.



		CITY OF KENT ENGINEERING DEPARTMENT	
		URBAN EYEBROW ON RESIDENTIAL STREET	
DESIGNED <u>COK</u>	SCALE <u>NONE</u>	STANDARD PLAN	
DRAWN <u>COK</u>	DATE <u>12/2019</u>	6-19	
CHECKED <u>COK</u>	ENGINEER		
APPROVED			