

**BOLLARD:**  
 FAIRWEATHER 4"X36" B-1 BOLLARD, 36" SURFACE MOUNT, WITH OUTLET.

COLOR: BLACK, CONTRACTOR SHALL SUBMIT COLOR CHIPS.

OUTLET BOX: ALUMINUM, SINGLE GANG CASE DEVICE BOX (OR EQUIVALENT)

GFCI RECEPTACLE: LEVITON 8898-T, 20A, 125V, NEMA 5-20R, 2P, 3W (OR EQUIVALENT)

OUTLET COVER AND GASKET PROVIDED BY BOLLARD MANUFACTURER

CARLON WEATHER PROOF COVER (PART #E9UVHMC) OR APPROVED EQUAL.

LEVEL BOLLARD BASE AS NECESSARY TO COMPENSATE FOR SIDEWALK CROSS SLOPE.


BOLLARD SHALL BE INSTALLED WITH OUTLET COVER FACING TOWARD THE STREET TREE, AT THE CENTER OF THE TREE GRATE

SEE STANDARD PLAN 6-55 FOR STREET TREE INSTALLATION INFORMATION

(1) 1" MIN. DIAMETER STEEL CONDUIT WITH 1/4" DIAMETER NYLON PULL ROPE  
 INSTALL 2-#10 WIRES WITH GROUND

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION IS KEPT ON FILE AT THE CITY OF KENT. A COPY MAY BE OBTAINED UPON REQUEST.



		<b>CITY OF KENT</b> ENGINEERING DEPARTMENT	
		<b>SIDEWALK BOLLARD WITH RECEPTACLE</b>	
DESIGNED: COK	SCALE: NONE	STANDARD PLAN	
DRAWN: COK	DATE: 12/2019	<b>6-56</b>	
CHECKED: COK	ENGINEER		
APPROVED:			