



KDCS = KENT DESIGN AND CONSTRUCTION STANDARDS.

NOTES:

1. SEE RETAINING WALLS AND ROCK FACINGS IN THE KDCS 6.11.C.
2. FACE OF WALL MUST BE OUTSIDE THE CLEAR ZONE AS SHOWN ON KENT STD. PLAN 6-50.
3. WSDOT TYPE 4 CHAIN LINK FENCE OR PEDESTRIAN RAILING REQUIRED WHEN WALL HEIGHT ABOVE FINISHED GRADE IS 30 IN. OR GREATER. SEE KENT STD. PLAN 6-41 OR WSDOT STD. PLAN L-20.10.
4. 8'-0" MAX. HEIGHT ADJACENT TO PUBLIC RIGHT-OF-WAY. 3'-0" TO 6'-0" MAX. HEIGHT ADJACENT TO OTHER PROPERTIES OR BETWEEN INTERIOR LOTS PER KENT STD. PLAN 6-57 .
5. CAST-IN-PLACE CONCRETE WALL HEIGHTS EXCEEDING 3'-0" IN HEIGHT ARE ALLOWED WHEN ADJACENT TO PUBLIC ROW. WALLS USED ON PRIVATE PROPERTY NOT ABUTTING PUBLIC ROW OVER 6'-0" IN HEIGHT ARE REQUIRED TO BE ENGINEERED.
6. DESIGN SIDEWALK CROSS GRADE SHALL BE 1.5%. CONSTRUCTION TOLERANCES SHALL BE 1% MIN AND 2% MAX.
7. SIGHT DISTANCE, ROAD GRADES AND ALIGNMENTS SHALL BE CONSIDERED IN DESIGN.
8. PIPE TO DRAIN TO CITY STORM SYSTEM OR NATURAL DRAINAGE COURSE.
9. PROVIDE EXPANSION JOINT PER KENT STD. PLAN 6-34.

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION IS KEPT ON FILE AT THE CITY OF KENT. A COPY MAY BE OBTAINED UPON REQUEST.



		CITY OF KENT ENGINEERING DEPARTMENT	
		WALLS IN CUT SECTION PUBLIC ROW	
DESIGNED <u>COK</u>	SCALE <u>NONE</u>	STANDARD PLAN	
DRAWN <u>COK</u>	DATE <u>12/2019</u>	6-60	
CHECKED <u>COK</u>	ENGINEER		
APPROVED			