



NOTES:

1. METAL POSTS SHALL BE TELES PAR POST STEEL PIPE TYPE, OR APPROVED EQUIVALENT.
2. FOR IN-SIDEWALK INSTALLATIONS, CORE AN 8" DIAMETER HOLE PRIOR TO EXCAVATION.
3. ANCHOR LENGTH SHALL BE 30", LENGTH MAY BE REDUCED TO 24" OR SIGN POST BASE PLATE INSTALLATION TYPE B (SEE DETAIL 6-82b) MAY BE USED; ONLY IF APPROVED BY THE CITY OF KENT. ANCHOR SHALL HAVE 4 EACH 7/16" DIAMETER HOLES ONE EACH SIDE 2" FROM TOP. FINISH SHALL BE ZINC HOT DIPPED GALVANIZED MATERIAL TO MEET ASTM A500 GRADE B, 7 GAUGE, 2 1/2"x 2 1/2" TELES PAR ANCHOR OR APPROVED EQUIVALENT.
4. POST SHALL BE ROLLED CARBON SHEET STEEL, ASTM A1011 GRADE 50 AND BE HOT DIPPED GALVANIZED AASHTO M120 YIELD STRENGTH 60,000 PSI MIN. SQUARE POST SHALL HAVE 7/16" DIAMETER PRE-PUNCHED HOLES ON 1" CENTERS FULL LENGTH, FOUR SIDES.
5. DRIVE RIVETS TO BE TL3806 3/8" DIAMETER
6. CORNER BOLTS TO BE TL070M. JAMNUTS TL062 AND 3/8" GALVANIZED WASHER WITH BLACK INSULATED WASHER.
7. SEE STANDARD PLAN 6-83M AND 6-84M FOR STREET NAME SIGN DETAILS.
8. PRIVATE STREET NAME SIGNS AND PRIVATE SIGN POSTS ARE MAINTAINED BY THE PROPERTY OWNERS.
9. ALUMINUM SIGN BLANK THICKNESS;
 WARNING AND REGULATORY 30" AND UNDER - 0.080".
 WARNING AND REGULATORY 36" AND OVER - 0.125"
10. SHEETING MATERIAL:
 WARNING AND REGULATORY - 3M HIGH INTENSITY PRISMATIC
 SCHOOL SIGNS - 3M DIAMOND GRADE DG3
 LEGENDS, SYMBOLS AND BORDERS - 3M ELECTROCUT FILM

NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE. THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION IS KEPT ON FILE AT THE CITY OF KENT. A COPY MAY BE OBTAINED UPON REQUEST.



		CITY OF KENT ENGINEERING DEPARTMENT	
		SIGN POST INSTALLATION TYPE A	
DESIGNED	COK	SCALE	NONE
DRAWN	COK	STANDARD PLAN	
CHECKED	COK	DATE	7/2020
APPROVED		ENGINEER	
			6-82a